

DENSO BUTYL 30 TAPE

UV Resistant Protective Pipeline Tape

Description

Denso Butyl 30 Tape is comprised of a UV resistant polymer backing and a butyl adhesive. It has a siliconized interleaving which is removed as the tape is applied. Available in white rolls.

Uses

Used as a long-term UV resistant corrosion protection tape for above or below ground pipeline and steel structures. It can also be used a protective outerwrap for Denso Petrolatum Tapes.

Features

- Long term UV resistance
- Excellent adhesion properties
- Easily applied with no special equipment
- Good conformability
- Compatible with common pipe coatings
- Cold applied
- Aesthetically pleasing
- Excellent resistance to cathodic disbonding
- Meets AWWA C209 Standard

Application

Prepare surfaces by removing all loose scale, rust or other foreign matter by grit blasting or wire brush. Surface must be clean, dry and free of grease. Peel back interleaving and apply adhesive side of the tape to the surface and press down. Apply the tape spirally with enough tension to make it conform. Remove interleaving as wrapping proceeds. Overlap each turn by at least 1" or 55% to achieve double thickness. If application temperature is 32°F or below, Denso Butyl Primer is recommended.

Irregular surfaces such as valves, flanges, etc. may require the use of Densyl Mastic or Denso Profiling Mastic. Refer to the product sheets for these specific products for information on application and selection.



Denso Butyl 30 Tape

Property Specifications

PROPERTIES

ENGLISH

Thickness (ASTM D1000)	30 mils
Weight	.14 lbs/ft ²
Tensile Strength (ASTM D822)	4821 psi (at break)
Peel Strength	17 lbs. per linear inch (adhesive)
UV Resistance	Excellent
Elongation @ Break (ASTM D822)	900%
Temperature Range	
Recommended Application	32°F to 110°F
Continuous Service	-40°F to 220°F
Breakdown Voltage	16 kV
Roll Width	2", 3", 4", 6"
Roll Length	75 ft

Quantity Estimates

Tape Width	Rolls ^a / Case	Coverage with 1" Overlap	Coverage with 50% Overlap
2"	24	150 ft ² /case	150 ft ² /case
4"	12	225 ft ² /case	150 ft ² /case
6"	8	250 ft ² /case	150 ft ² /case

All rolls are 75 feet in length.

Other roll widths are available on request.



DENSO NORTH AMERICA

HOUSTON:
9747 Whithorn Drive,
Houston, Texas,
U.S.A. 77095
Tel: 281-821-3355
Fax: 281-821-0304

TORONTO:
90 Ironside Crescent,
Unit 12, Toronto,
Ontario, Canada M1X1M3
Tel: 416-291-3435
Fax: 416-291-0898

www.densona.com

A Member of Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be