

Denso®

Protal Pipeline Coatings

Protective Liquid Coatings



Uses & Applications

- Liquid coating of girth welds and tie-ins
- Liquid coating of welds for boring applications
- Repairs to FBE, fittings and fabrication
- Rehabilitation of existing pipelines
- Coating of cadweld areas





Protal Pipeline Coatings



Protal 7125 being brush applied in arctic temperature conditions.



Protal ARO being spray applied.



Protal Repair Cartridge application.

- ### Features
- Easy to apply (brush, roller or spray)
 - Fast cure
 - High build (up to 70 mils in one coat)
 - Outstanding cathodic disbondment results (6mm @ 203°F)
 - Excellent adhesion (compliments FBE coated pipe)
 - High abrasion resistance for drilling applications
 - 100% solids (no solvents)
 - Safe and environmentally responsible
 - Does not shield cathodic protection



Pipe coated with 30 mils of Protal 7900HT.



DENSO NORTH AMERICA

HOUSTON:
 9747 Whithorn Drive,
 Houston, Texas,
 U.S.A. 77095
 Tel: 281-821-3355
 Fax: 281-821-0304

TORONTO:
 90 Ironside Crescent,
 Unit 12, Toronto,
 Ontario, Canada M1X1M3
 Tel: 416-291-3435
 Fax: 416-291-0898

e-mail: info@densona.com

www.densona.com

A Member of Winn & Coales International