

DENSO POLY-WRAP

Clear Outerwrap Used Over Petrolatum Tape Systems

Description

Denso Poly-Wrap is a 150 gauge (1.5 mil) wrap made from high performance metallocene resins.

Uses

Used as an outerwrap for Denso Petrolatum Tape Systems for straight pipe and irregular fittings and valves.

Features

- Superior holding force
- Excellent prestretch up to 250%
- Excellent conformability to irregular shapes
- High dielectric strength
- Adds puncture resistance

Application

The Poly-Wrap shall be spirally wrapped using sufficient tension to wrap over the Denso Petrolatum Tape.



Denso Poly-Wrap

Property Specifications

PROPERTIES	ENGLISH
Elongation MD (ASTM D882)	500%
Elongation TD (ASTM D882)	725%
Tensile Ult. MD psi (ASTM D882)	7600
Tensile Ult. TD psi (ASTM D882)	6000
Tensile Ult. TD psi (ASTM D882)	6000
Thickness	1.5 mils
Roll Width	4", 6", and 12"
Roll Length	550 ft

Quantity Estimates

Tape Width	Rolls/ Case	Coverage with 50% Overlap
4"	6	550 ft ² /case
6"	4	550 ft ² /case
12"	2	550 ft ² /case

** All rolls are 550 feet in length.*



DENSO NORTH AMERICA

HOUSTON:
9747 Whithorn Drive,
Houston, Texas,
U.S.A. 77095
Tel: 281-821-3355
Fax: 281-821-0304

TORONTO:
90 Ironside Crescent,
Unit 12, Toronto,
Ontario, Canada M1X1M3
Tel: 416-291-3435
Fax: 416-291-0898

www.densona.com

A Member of Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.