

# **DENSO PRIMER D**

## **Bitumen Tape Primer**

### **Description**

Denso Primer D is an oxidized bitumen in aliphatic and aromatic hydrocarbon solvents.

### **Uses**

A fast drying bitumen based primer for all surfaces prior to the application of Denso bitumen tapes.

### **Features**

- Fills surface irregularities for intimate contact of tape compound
- Promotes high adhesion
- Fast drying
- Good penetration characteristics
- Can be brush or spray applied

### **Application**

Prepare surfaces by removing all loose scale, rust or other foreign matter by grit blasting or wire brush. Apply a thin uniform coat of Denso Primer D to clean surface and allow to tack dry. Drying time will be dependent on surface temperature.

**Denso**<sup>®</sup>



# Denso Primer D

## Property Specifications

<b>PROPERTIES</b>	<b>ENGLISH</b>	<b>METRIC</b>
Specific Gravity	.94	.94
Drying Time	10 - 15 min @ 68°F	10 - 15 min @ 20°C
Flash Point	73°F	23°C
Maximum Service Temperature	170°F	77°C
Coverage Capacity	592 ft <sup>2</sup> /1.3 gallon	55 m <sup>2</sup> /5 liters

### COVERAGE:

2,368 ft<sup>2</sup> per case  
(220 m<sup>2</sup> per case)

Note: Porous surfaces may yield less coverage.

### PACKAGING:

4 each 1.3 gallon containers per case  
(4 each 5 liter containers per case)



### DENSO NORTH AMERICA

**HOUSTON:**  
9747 Whithorn Drive,  
Houston, Texas,  
U.S.A. 77095  
Tel: 281-821-3355  
Fax: 281-821-0304

**TORONTO:**  
90 Ironside Crescent,  
Unit 12, Toronto,  
Ontario, Canada M1X1M3  
Tel: 416-291-3435  
Fax: 416-291-0898

[www.densona.com](http://www.densona.com)

**A Member of Winn & Coales International**

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.